



RA12-70S(12V70Ah)

Specification





Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	70Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 21.5 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 6.0 mΩ
Terminal	F15(M6)/F11(M6)
Max. Discharge Current	700A (5 sec)
Short Circuit Current	1480A
Design Life	12 years (Float charging)
Max. Charging Current	21.0 A
Reference Capacity	C3 53.7AH C5 60.5AH C10 70.0AH C20 74.2AH
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RA series is a general purpose battery with 12 years design life in float service. It meets with IEC, JIS, BS, GB/T and YD/T standards. With advanced AGM valve regulated technology and high purity raw material, the RA series battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, Telecom, power grid, medical equipment, emergency light and security system applications.



Dimensions



F11 TERMINAL

Length	260±2mm (10.2 inches)
Width	169±2mm (6.65 inches)
Height	211±2mm (8.31 inches)
Total Height	216±2mm (8.50 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	165.7	127.2	75.9	42.8	25.2	19.5	15.4	13.1	8.86	7.38	3.86
1.65V	156.6	121.6	72.9	41.3	24.4	18.9	15.0	12.8	8.76	7.29	3.80
1.70V	144.2	113.9	69.6	40.0	23.6	18.4	14.6	12.5	8.62	7.18	3.76
1.75V	132.0	106.0	66.6	38.5	22.8	17.9	14.2	12.1	8.50	7.09	3.71
1.80V	119.5	97.9	63.6	37.0	22.0	17.3	13.8	11.8	8.36	7.00	3.67
1.85V	97.6	81.2	54.8	33.2	20.1	16.0	12.8	11.0	7.85	6.59	3.49

Constant Power Discharge Characteristics : WPC (25°C)


F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	281.7	222.4	137.8	80.4	47.8	37.3	29.6	25.3	17.3	14.5	7.61
1.65V	271.3	215.7	133.7	78.1	46.5	36.3	28.9	24.7	17.1	14.4	7.50
1.70V	254.4	205.1	129.1	76.0	45.2	35.5	28.2	24.2	16.9	14.2	7.41
1.75V	237.0	193.6	124.7	73.7	43.8	34.6	27.6	23.7	16.7	14.0	7.33
1.80V	218.3	181.3	120.4	71.3	42.5	33.7	26.9	23.1	16.5	13.8	7.27
1.85V	181.6	152.6	104.7	64.3	39.1	31.2	25.1	21.6	15.5	13.0	6.91

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C10 should reach 95% after the first cycle and 100% after the third cycle.


RA12-70S(12V70Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.